

# CANOPY

## DL-C

### LED LUMINAIRE

- Optical:** 100-115 Lm/Watt, 2700k – 6000k, CRI 70, (Patent Pending optics)
- Electrical:** 120 – 277v, 347v, or 480v AC, 12/24v DC, 0.7 A, 20w to 300w, Dimmable
- Mechanical:** Aluminum Housing, 12" W x 13-30" L by 2 1/4" high, powder coated
- Certifications/Ratings:** CETL/CUL, ROHS, IP65 Rated, DLC
- Reliability:** "EncapsLED" heat sink for superior cooling and durability (patent pending), Warranty: 5 yrs.
- Options:** Dimming (D); Motion Sensor (M); Smart Controls (S) to optimize energy savings



\*Premium Edition

Model #	System Wattage	5,000k Lumens	Model #	System Wattage	5,000k Lumens
DL-C-30w	30	3,000	DL-C-170w	170	17,000
DL-C-40w	40	4,000	DL-C-180w	180	18,000
DL-C-50w	50	5,000	DL-C-190w	190	19,000
DL-C-60w	60	6,000	DL-C-200w	200	20,000
DL-C-70w	70	7,000	DL-C-210w	210	21,000
DL-C-80w	80	8,000	DL-C-220w	220	22,000
DL-C-90w	90	9,000	DL-C-230w	230	23,000
DL-C-100w	100	10,000	DL-C-240w	240	24,000
DL-C-110w	110	11,000	DL-C-250w	250	25,000
DL-C-120w	120	12,000	DL-C-260w	260	26,000
DL-C-130w	130	13,000	DL-C-270w	270	27,000
DL-C-140w	140	14,000	DL-C-280w	280	28,000
DL-C-150w	150	15,000	DL-C-290w	290	29,000
DL-C-160w	160	16,000	DL-C-300w	300	30,000



USA Made



### Ordering Information

Example: DL-C-50w-P-5000-5W-S-N-277v

Model#	Mounting	Color Temp	Lens Type*	Finish	Options	Voltage
DL-C-wattage (30- 300w)	Insert (I) Surface (S)	2,700 - 6,000	5W,5M 5N	White, Bronze, Silver	None(N), Dimmable(D) Smart System(S)	120– 277v, 347v-480v

\*Lens 5W=150 degrees, 5M=120 degree, 5N= 40 degrees